



## Safety Data Sheet

Version number: 10.1  
SDS# K8503

2021-08-12

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **K-8503 Ampoules, R-8515**  
Other means of identification Phosphate Vacu-vials® Ampoules and CHEMetrics® Refill

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Component of water analysis test kits: K-8503, K-8515, K-8530

#### 1.3 Details of the supplier of the safety data sheet

CHEMetrics, Inc.  
4295 Catlett Road  
Midland VA 22728  
United States

Telephone: 1-540-788-9026  
Telefax: 1-540-788-4856  
e-mail: technical@chemetrics.com  
Website: www.chemetrics.com

#### 1.4 Emergency telephone number

Emergency information service ChemTel Inc.: 1-800-255-3924, +01-813-248-0585

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.6	carcinogenicity	1A	Carc. 1A	H350
3.7	reproductive toxicity	2	Repr. 2	H361
3.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
4.1A	hazardous to the aquatic environment - acute hazard	3	Aquatic Acute 3	H402
4.1C	hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16.

## 2.2 Label elements

### Labeling

- Signal word            danger

- Pictograms

GHS05, GHS07, GHS08,  
GHS09



- Hazard statements

H314	Causes severe skin burns and eye damage.
H332	Harmful if inhaled.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

- Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dusts or mists.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

## Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
water	CAS No 7732-18-5	≥ 81		
sulfuric acid	CAS No 7664-93-9	16	Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 Carc. 1A / H350	
Ammonium molybdate tetrahydrate	CAS No 12054-85-2	2		
ammonium metavanadate	CAS No 7803-55-6	≤ 1	Acute Tox. 3 / H301 Acute Tox. 4 / H332 Eye Irrit. 2 / H319 Repr. 2 / H361 STOT RE 1 / H372	

For full text of abbreviations: see SECTION 16.

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Water jet

## 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

## 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

**Wear impact- and splash-resistant eyewear. Break the ampoule tip only when it is completely immersed in sample. Breaking the tip in air may cause the glass ampoule to shatter.**

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas. Never add water to this product.

- Handling of incompatible substances or mixtures

Do not mix with alkali.

- Keep away from

Caustic solutions

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

## 7.2 Conditions for safe storage, including any incompatibilities

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

## 7.3 Other information

**For optimum analytical performance, store in the dark and at room temperature.**

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	sulfuric acid	7664-93-9	PEL (CA)		0.1		3				Cal/ OSHA PEL
US	sulfuric acid	7664-93-9	REL		1 (10 h)						NIOSH REL
US	sulfuric acid	7664-93-9	PEL		1						29 CFR 1910.1000
US	sulfuric acid	7664-93-9	TLV®		0.2					t	ACGIH® 2021

Notation

Ceiling-C

STEL

t

TWA

ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

thoracic fraction

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
sulfuric acid	7664-93-9	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
sulfuric acid	7664-93-9	DNEL	0.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
ammonium metavanadate	7803-55-6	DNEL	0.64 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
ammonium metavanadate	7803-55-6	DNEL	0.18 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
ammonium metavanadate	7803-55-6	DNEL	0.92 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
sulfuric acid	7664-93-9	PNEC	0.003 mg/l	aquatic organisms	freshwater	short-term (single instance)
sulfuric acid	7664-93-9	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
sulfuric acid	7664-93-9	PNEC	8.8 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sulfuric acid	7664-93-9	PNEC	0.002 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sulfuric acid	7664-93-9	PNEC	0.002 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ammonium metavanadate	7803-55-6	PNEC	7.6 µg/l	aquatic organisms	freshwater	short-term (single instance)
ammonium metavanadate	7803-55-6	PNEC	2.5 µg/l	aquatic organisms	marine water	short-term (single instance)
ammonium metavanadate	7803-55-6	PNEC	450 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ammonium metavanadate	7803-55-6	PNEC	240 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ammonium metavanadate	7803-55-6	PNEC	79 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ammonium metavanadate	7803-55-6	PNEC	7.2 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

## Skin protection

### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

## Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Product description** Vacu-vials Ampoules: Sealed glass ampoules, 13 mm OD, for instrumental colorimetric water analysis. Each Vacu-vial™ ampoule contains approximately 0.8 - 2 mL of liquid reagent sealed under vacuum. Test kits contain 30 ampoules.

CHEMets Refills: Sealed glass ampoules, 7 mm OD, for visual colorimetric water analysis. Each CHEMet™ ampoule contains approximately 0.2 - 0.5 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

### Appearance

Physical state	liquid
Color	pale yellow
Particle	not relevant (liquid)
Odor	odorless

### Other safety parameters

pH (value)	<1 (acid)
Melting point/freezing point	0 °C
Initial boiling point and boiling range	120 °C
Flash point	not determined
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	not determined

Density	not determined
Vapor density	this information is not available
Relative density	1.08 (water = 1)

## Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

## Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

### 10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Harmful if inhaled.

#### - Acute toxicity estimate (ATE)

Inhalation: vapor 18.75 mg/l/4h

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
sulfuric acid	7664-93-9	inhalation: vapor	3 mg/l/4h
sulfuric acid	7664-93-9	inhalation: dust/mist	0.85 mg/l/4h
ammonium metavanadate	7803-55-6	oral	218.1 mg/kg
ammonium metavanadate	7803-55-6	inhalation: dust/mist	2.61 mg/l/4h

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
sulfuric acid	7664-93-9	1	

#### Legend

1 Carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens			
Name of substance	CAS No	Classification	Number
sulfuric acid	7664-93-9	Known to be a human carcinogen	9th Report on Carcinogens

#### Reproductive toxicity

Suspected of damaging the unborn child. Suspected of damaging fertility.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sulfuric acid	7664-93-9	EC50	>100 mg/l	aquatic invertebrates	48 h
sulfuric acid	7664-93-9	ErC50	>100 mg/l	algae	72 h
ammonium metavanadate	7803-55-6	LC50	9,005 µg/l	fish	24 h
ammonium metavanadate	7803-55-6	ErC50	2,907 µg/l	algae	72 h
ammonium metavanadate	7803-55-6	EC50	989.4 µg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ammonium metavanadate	7803-55-6	EC50	>100 mg/l	microorganisms	3 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Endocrine disrupting properties**

Information on this property is not available.

**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

please consider the relevant national or regional provisions

**SECTION 14: Transport information****14.1 UN number**

DOT	UN 3264
IMDG-Code	UN 3264
ICAO-TI	UN 3264

**14.2 UN proper shipping name**

	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (contains: sulfuric acid, ammonium metavanadate), 8, II, environmentally hazardous
DOT	Corrosive liquid, acidic, inorganic, n.o.s.
IMDG-Code	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.
Technical name (hazardous ingredients)	sulfuric acid, ammonium metavanadate

**14.3 Transport hazard class(es)**

DOT	8
IMDG-Code	8
ICAO-TI	8

**14.4 Packing group**

DOT	II
IMDG-Code	II
ICAO-TI	II

**14.5 Environmental hazards**

hazardous to the aquatic environment

Environmentally hazardous substance (aquatic environment)      sulfuric acid

#### 14.6 Other relevant information

Shipping container markings and labels, received from CHEMetrics, may vary from the above information. Products that are regulated for transport will be packaged by CHEMetrics as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations. CHEMetrics may also elect to ship certain products as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III. In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

##### **Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Reportable quantity (RQ)	6,250 lbs (2,838 kg) (sulfuric acid) (ammonium metavanadate)
Danger label(s)	8, fish and tree
	
Environmental hazards	YES (hazardous to the aquatic environment)
Special provisions (SP)	386, B2, IB2, T11, TP2, TP27
ERG No	154

##### **International Maritime Dangerous Goods Code (IMDG) - Additional information**

Marine pollutant	YES (hazardous to the aquatic environment) (sulfuric acid)
Danger label(s)	8, fish and tree
	
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Segregation group	1 - Acids

**International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	8
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations specific for the product in question****National regulations (United States)****Superfund Amendment and Reauthorization Act (SARA TITLE III )**

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities				
Name of substance	CAS No	Notes	Reportable quantity (pounds)	Threshold planning quantity (pounds)
sulfuric acid	7664-93-9		1,000	1000

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
sulfuric acid	7664-93-9	acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size	1986-12-31

**Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)**

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sulfuric acid	7664-93-9		1	1000 (454)
ammonium metavanadate	7803-55-6		4	1000 (454)

**Legend**

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act  
 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

**Clean Air Act**

none of the ingredients are listed

**Right to Know Hazardous Substance List**

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
sulfuric acid	7664-93-9		CA CO R2
ammonium metavanadate	7803-55-6		

**Legend**

CA Carcinogenic  
CO Corrosive  
R2 Reactive - Second Degree

**California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987**

none of the ingredients are listed

**Industry or sector specific available guidance(s)****NPCA-HMIS® III**

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

**NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

## National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**List of relevant phrases (code and full text as stated in chapter 2 and 3)**

Code	Text
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.